

**Appl. No. 10/695,707
Amdt. dated July 11, 2006
Reply to office action of April 26, 2006**

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently amended) A processor-based method of combining valuations of multiple choices from each of multiple evaluators, the method comprising:
for each evaluator,
 sorting the choices into an order that indicates preference;
 determining interval sizes between choice valuations;
 obtaining a rank for each interval size; and
 using interval size ranks, at least in part, to determine an evaluator score for each choice; and
combining evaluator scores for each choice to determine, at least in part, an overall score for each choice; and
presenting to a user a list of choices ordered in accordance with the overall scores.
2. (Original) The method of claim 1, wherein said obtaining a rank for each interval size comprises ranking interval sizes from smallest to largest.
3. (Original) The method of claim 1, wherein said using interval size ranks to determine an evaluator score for each choice comprises:
 associating a predetermined score with a first choice; and
 iteratively calculating a score for each subsequent choice by combining the score of a preceding choice with an increment based on the rank of the interval size between the preceding choice and said subsequent choice.
4. (Original) The method of claim 1, further comprising:
 determining equivalence classes for choices based on choice valuations, wherein said determining equivalence classes precedes said

Appl. No. 10/695,707
Amdt. dated July 11, 2006
Reply to office action of April 26, 2006

obtaining a rank for each interval size, and wherein said obtaining a rank for each interval size involves obtaining a rank for each interval size between valuations associated with different equivalence classes;

calculating scores for equivalence classes based on said interval size ranks; and

associating the score for each equivalence class with each choice that is a member of that equivalence class.

5. (Original) The method of claim 4, wherein said determining equivalence classes is based on a statistical interval distribution.

6. (Original) The method of claim 4, wherein said determining equivalence classes is based on a predetermined minimum interval size.

7. (Original) The method of claim 4, further comprising: generating a valuation to associate with each equivalence class by operating on the one or more valuations associated with the one or more choices in that equivalence class, said operating using an operator from a group consisting of:

an arithmetic mean of the one or more valuations;

a geometric mean of the one or more valuations;

a harmonic mean of the one or more valuations;

a root mean square of the one or more valuations;

a median of the one or more valuations;

a value corresponding to a predetermined percentile among the one or more valuations;

a most frequent valuation of the one or more valuations;

a most frequent valuation determined within a predetermined precision;

a maximum of the one or more valuations; and

a minimum of the one or more valuations.

Appl. No. 10/695,707
Amdt. dated July 11, 2006
Reply to office action of April 26, 2006

8. (Original) The method of claim 1, further comprising:
assigning an adverse valuation to each choice not evaluated by a given evaluator, wherein the adverse valuation indicates that the choice is less preferred than the least preferred choice evaluated by the given evaluator, and wherein the adverse valuation separates the choice from the least preferred choice by an interval greater than each other interval between adjacent choice valuations.
9. (Original) The method of claim 1, wherein said ranking includes:
assigning equalized ranks to intervals that are substantially equal.
10. (Original) The method of claim 1, wherein the overall score for each choice is a weighted or unweighted sum of evaluator scores for that choice.
11. (Original) The method of claim 1, wherein said combining includes:
scaling evaluator scores to a uniform range.
12. (Original) The method of claim 1, wherein said combining includes:
scaling evaluator scores to provide each evaluator with an equal sum of evaluator scores.
13. (Original) The method of claim 1, further comprising:
selecting a predetermined number of choices having the most favorable overall scores.
14. (Original) The method of claim 1, further comprising:
selecting from a group of choices a predetermined number of choices having the most favorable overall scores.

Appl. No. 10/695,707
Amdt. dated July 11, 2006
Reply to office action of April 26, 2006

15. (Original) The method of claim 1, further comprising:
 sorting the choices according to the overall score determined for each choice.
16. (Original) The method of claim 1, wherein at least one of the evaluators is selected from a group consisting of:
 a provider of values derived from sensor measurements,
 a provider of values derived from performance measurements,
 a provider of values derived from solicited personal opinions,
 a provider of values derived by a Bayesian network,
 a provider of values derived by a decision tree,
 a provider of values derived by an evolved algorithm,
 a provider of values derived by a neural network,
 a provider of values derived by a fitness estimator, and
 a provider of values derived from complexity measurements.
17. (Original) The method of claim 1, wherein each choice represents an alternative from a group consisting of:
 classifications of an item;
 candidate solutions to a problem;
 contest competitors; and
 features to be used for classification.
18. (Currently amended) A system for combining valuations of multiple choices from each of multiple evaluators, wherein the choices are different classifications and the valuations represent probabilities that a web site visitor belongs that classification, the system comprising:
 a processor; and
 a memory coupled to the processor and configured to provide the processor with software that configures the processor to iterate

Appl. No. 10/695,707
Amdt. dated July 11, 2006
Reply to office action of April 26, 2006

through the multiple evaluators, and for each evaluator configures the processor to:
obtain ranks of intervals between a valuation-ordered group of choices;
and
determine a score for each choice from the interval ranks[.];
~~wherein the software further configures the processor to combine choice~~
scores for each evaluator to obtain an overall score for each choice; and
select the choice having the highest overall score as the classification for the web site visitor.

19. (Original) The system of claim 18, wherein the software further configures the processor to retrieve choice valuations from at least one external evaluator.
20. (Original) The system of claim 18, wherein the software further configures the processor to operate as at least one evaluator.
21. (Original) The system of claim 18, wherein the software further configures the processor to employ one or more of the choices in a manner responsive to the overall scores.
22. (Original) The system of claim 18, wherein as part of configuring the processor to rank intervals, the software configures the processor to assign a rank of zero to intervals of insignificant size.
23. (Original) The system of claim 18, wherein as part of configuring the processor to determine a score for each choice, the software configures the processor to:
determine equivalence classes for choices based on choice valuations before obtaining ranks of intervals, wherein said obtaining

Appl. No. 10/695,707
Amdt. dated July 11, 2006
Reply to office action of April 26, 2006

comprises finding ranks of the intervals between valuations associated with the equivalence classes;
calculate scores for equivalence classes based on the interval ranks; and
associate the score for each equivalence class with each choice that is a member of that equivalence class.

24. (Original) The system of claim 18, wherein the software further configures the processor to assign an adverse valuation to each of an evaluator's unevaluated choices, wherein the adverse valuation indicates that the choice is less preferred than the least preferred choice evaluated by that evaluator, and wherein the interval between the least preferred choice and the unevaluated choice no smaller than each interval between that evaluator's evaluated choices.
25. (Original) The system of claim 18, wherein as part of configuring the processor to rank intervals, the software configures the processor to assign equalized ranks to intervals that are substantially equal.
26. (Original) The system of claim 18, wherein as part of configuring the processor to combine choice scores, the software configures the processor to scale choice scores to a uniform range.
27. (Original) The system of claim 18, wherein as part of configuring the processor to combine choice scores, the software configures the processor to scale choice scores to provide each evaluator with an equal sum of choice scores.
28. (Original) The system of claim 18, wherein the overall scores for each choice are weighted or unweighted sums of the scores for each choice.

Appl. No. 10/695,707
Amdt. dated July 11, 2006
Reply to office action of April 26, 2006

29. (Currently amended) An evaluation system for ranking a company's products comprising:

- a means for determining a valuation by each of multiple evaluators for each of multiple ~~choices~~ products, wherein at least one evaluator determines a valuation representing revenue, and another evaluator determines a valuation representing profit;
- a means for ranking intervals between valuation-ordered ~~choices~~ products for each evaluator;
- a means for determining ~~choice~~ product scores using interval ranks for each evaluator;
- a means for combining ~~choice~~ product scores to determine an overall score for each ~~choice~~ product; and
- a means for selecting a predetermined number of ~~choices~~ products in accordance with their overall scores.

30. (Currently amended) The ~~method~~ system of claim 29, wherein said means for determining ~~choice~~ product scores comprises:

- a means for associating a predetermined score with a first ~~choice~~ product; and
- a means for iteratively calculating a score for each subsequent ~~choice~~ product by combining the score of a preceding ~~choice~~ product with an increment based on the rank of the interval size between the preceding ~~choice~~ product and said subsequent ~~choice~~ product.

31. (Currently amended) An information carrier medium configurable to provide a computing device with software for combining valuations of multiple choices from each of multiple evaluators, wherein the software configures the computing device to:

- for each evaluator,
 - sort the choices into an order that indicates preference;
 - determine interval sizes between choice valuations;

Appl. No. 10/695,707
Amdt. dated July 11, 2006
Reply to office action of April 26, 2006

obtain a rank for each interval size; and
determine from the interval size ranks an evaluator score for each
choice; and
combine evaluator scores for each choice to determine an overall score
for each choice; and
display a list of choices ordered in accordance with overall scores.

32. (Original) The medium of claim 31, wherein as part of configuring the computing device to determine an evaluator score for each choice, the software configures the computing device to:

associate a predetermined score with a first choice; and
iteratively calculate a score for each subsequent choice by combining the score of a preceding choice with an increment based on the rank of the interval size between the preceding choice and said subsequent choice.

33. (Original) The medium of claim 31, wherein the software further configures the computing device to:

determine equivalence classes for choices based on choice valuations before obtaining a rank for each interval size, wherein said obtaining a rank for each interval size involves obtaining a rank for each interval size between valuations associated with different equivalence classes;
calculate scores for equivalence classes based on said interval size ranks; and
associate the score for each equivalence class with each choice that is a member of that equivalence class.